


Ordering code PA 430

PA 430



Standard version		8	5	0																
Analogue output																				
	4 ... 20 mA / 2-wire				1															
	0 ... 10 V / 3-wire				3															
Intrinsic safety for zone 1 / 4 ... 20 mA / 2-wire customer					E															on request
Contact ¹																				
	without contact				0															
	1 contact				1															
	2 contacts				2															
Electrical connection (output)																				
	ISO 4400					1	0	0												
	Binder series 723 (5-pin)					2	0	0												
	Binder series 723 (7-pin) ²					A	0	1												
	M12x1 (5-pin) / metal version					N	1	0												
Electrical connection (input)																				
	ISO 4400						1	0	0											
	Binder series 723 (5-pin)						2	0	0											
	Binder series 723 (7-pin)						A	0	1											
	M12x1 (5-pin) / metal version						N	1	0											
Unit																				
	without ³								0											
	bar								1											
	mbar								2											
	mH ₂ O								3											
	%								P											
	mA								A											
	customer								9											on request
Label on display																				
	standard								1											
	neutral								N											
	customer								9											on request
Special version																				
	standard											0	0	0						
	customer											9	9	9						on request

¹ max. 1 contact for: 4 ... 20 mA / 2-wire with plug ISO 4400; 0 ... 10 V / 3-wire with Binder 723 (5-pin) or M12x1 (5-pin); Ex-protection no contact possible with 0 ... 10 V / 3-wire with plug ISO 4400
² intended for the use with DMP 331i, DMP 333i and LMP 331i with el. connection Binder Serie 723 (7-pin)
³ the unit signs are loose-settled

This ordering code contains product specification; properties are not guaranteed. Subject to change without notice.

