

Ordering code DMP 304

DMP 304

□	□	□	-	□	□	□	-	□	-	□	-	□	□	□	-	□	□	□
---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---	---

Pressure																		
	gauge	2	2	0														
Input																		
	[bar]																	
	2 000				2	0	0	4										
	4 000				4	0	0	4										
	5 000				5	0	0	4										
	6 000				6	0	0	4										
	customer				9	9	9	9										consult
Output																		
	4 ... 20 mA / 2-wire								1									
	Intrinsic safety 4 ... 20 mA / 2-wire								E									consult
	0 ... 10 V / 3-wire								3									consult
	customer								9									consult
Accuracy																		
	standard	0.5 %							5									
	option	0.25 %							2									consult
	customer								9									consult
Electrical connection																		
	Male and female plug ISO 4400								1	0	0							
	Male plug Binder series 723 (5-pin)								2	0	0							
	Cable outlet with PVC-cable ¹								T	A	0							
	Cable outlet ²								T	R	0							
	Male plug M12x1 (4-pin)								M	0	0							
	MIL-/Bendix (Typ PT 02 A 10-6 P)								B	G	0							consult
	customer								9	9	9							consult
Mechanical connection																		
	9/16" UNF internal thread									V	0	0						
	M16x1.5 internal thread									P	0	0						
	M20x1.5 internal thread									D	2	8						
	customer									9	9	9						consult
Special version																		
	adjustable																	0 4 1
	customer																	9 9 9

¹ standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C), optionally cable with ventilation tube
² different cable types and lengths deliverable (permissible temperature depends on kind of cable)

This price list contains product specification, properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.

