

DMP 343 选型表

DMP 343

测量压力		表压	1	0	0															
额定量程		[mbar]																		
	10		0	1	0	0														
	16		0	1	6	0														
	25		0	2	5	0														
	40		0	4	0	0														
	60		0	6	0	0														
	100		1	0	0	0														
	160		1	6	0	0														
	250		2	5	0	0														
	400		4	0	0	0														
	600		6	0	0	0														
	1000		1	0	0	1														
	-1000 ... 0		X	1	0	2														
	用户需求		9	9	9	9														请咨询
输出																				
	4 ... 20 mA / 2线制																			1
	0 ... 20 mA / 3线制																			2
	0 ... 10 V / 3线制																			3
	本安防爆 4 ... 20 mA / 2线制																			E
	用户需求																			9
精度 (根据 BFSL)																				
	标准 P _N > 100 mbar	0.175%																		3
	标准 P _N ≤ 100 mbar	0.25%																		5
电气连接																				
	ISO 4400 插头与插座																			1 0 0
	Binder Serie 723 (5针)																			2 0 0
	线缆出口配PVC线缆 ¹																			T A 0
	线缆出口 ²																			T R 0
	M12x1 (4 针) / 金属																			M 1 0
	紧凑型防护壳 不锈钢1.4305																			8 5 0
	用户需求																			9 9 9
压力接口及过程连接件																				
	G1/2" DIN 3852																			1 0 0
	G1/2" EN 837																			2 0 0
	G1/4" DIN 3852																			3 0 0
	G1/4" EN 837																			4 0 0
	G1/2" DIN 3852 开放式压力接口																			H 0 0
	1/2" NPT																			N 0 0
	1/4" NPT																			N 4 0
	用户需求 ³																			9 9 9
密封件																				
	FKM																			1
	用户需求																			9
特殊型号																				
	标准																			0 0 0
	用户需求																			9 9 9

¹ 标准: 2mPVC线缆不带大气管 (工作温度: -5 ... 70°C), 可选线缆带大气管
² 线缆带大气管 (TR0=PVC线缆), 各种型号和长度的线缆可供选择, 价格不包含线缆
³ 公制螺纹及其他请咨询

本数据资料仅用于描述产品技术参数, 并不保证技术性能。所作任何修改恕不另行通知。