

Ordering code DMD 341

DMD 341

□□□ - □□□□ - □ - □ - □□□ - □□□ - □ - □□□

Pressure										
	differential pressure	3	3	0						
	gauge pressure	3	3	1						
Input [mbar]										
	6	0	0	6	0					
	10	0	1	0	0					
	20	0	2	0	0					
	40	0	4	0	0					
	60	0	6	0	0					
	100	1	0	0	0					
	160	1	6	0	0					
	250	2	5	0	0					
	400	4	0	0	0					
	600	6	0	0	0					
	1000	1	0	0	1					
	-6 ... 6	S	0	0	6					consult
	-10 ... 10	S	0	1	0					consult
	-20 ... 20	S	0	2	0					consult
	-40 ... 40	S	0	4	0					consult
	-60 ... 60	S	0	6	0					consult
	-100 ... 100	S	1	0	0					consult
	-160 ... 160	S	1	6	0					consult
	-250 ... 250	S	2	5	0					consult
	-400 ... 400	S	4	0	0					consult
	-600 ... 600	S	6	0	0					consult
	-1000 ... 1000	S	1	0	2					consult
	customer	9	9	9	9					consult
Output										
	4 ... 20 mA / 2-wire					1				
	0 ... 20 mA / 3-wire ¹					2				
	0 ... 10 V / 3-wire					3				
	(12 ± 8) mA / 2-wire					S1				consult
	(10 ± 10) mA / 3-wire ¹					S2				consult
	(5 ± 5) V / 3-wire					S3				consult
	customer					9				consult
Accuracy										
	standard for P _N > 160 mbar	0,35 %				3				
	Standard for 40 mbar ≤ P _N ≤ 160 mbar	1,0 %				8				
	standard for P _N < 40 mbar	2,0 %				G				
	customer					9				consult
Electrical connection										
	Male and female plug ISO 4400					1	0	0		
	Male plug M12x1 (4-pin)					M	0	0		
	Cable outlet with PVC cable ²					T	A	0		
	customer					9	9	9		consult
Mechanical connection										
	G1/8" internal thread						Q	0	0	
	Ø6.6 x 11 (for flex. tubes Ø6)						Y	0	0	
	customer						9	9	9	consult
Seals										
	PUR, bonded								6	
Special version										
	standard								0	0
	customer								9	9
										consult

¹ not possible in combination with display and switching module ASM 430
² standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70 °C)

This price list contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.

