

**Ordering code DMK 331**

**DMK 331**

□□□ - □□□□ - □ - □ - □□□ - □□□ - □ - □ - □□□

<b>Pressure</b>										
gauge	2	5	0							
absolute	2	5	1							
<b>Input</b>										
[bar]										
0.40	4	0	0	0						
0.60	6	0	0	0						
1.0	1	0	0	1						
1.6	1	6	0	1						
2.5	2	5	0	1						
4.0	4	0	0	1						
6.0	6	0	0	1						
10	1	0	0	2						
16	1	6	0	2						
25	2	5	0	2						
40	4	0	0	2						
60	6	0	0	2						
100	1	0	0	3						
160	1	6	0	3						
250	2	5	0	3						
400	4	0	0	3						
600	6	0	0	3						
-1 ... 0	X	1	0	2						
customer	9	9	9	9						consult
<b>Output</b>										
4 ... 20 mA / 2-wire					1					
0 ... 20 mA / 3-wire					2					
0 ... 10 V / 3-wire					3					
Intrinsic safety 4 ... 20 mA / 2-wire					E					
SIL2 4 ... 20 mA / 2-wire					1S					
SIL2 with Intrinsic safety					ES					
4 ... 20 mA / 2-wire										
customer					9					consult
<b>Accuracy</b>										
0.5 %					5					
customer					9					consult
<b>Electrical connection</b>										
Male and female plug ISO 4400					1	0	0			
Male plug Binder series 723 (5-pin)					2	0	0			
Cable outlet with PVC cable <sup>1</sup>					T	A	0			
Cable outlet with cable					T	R	0			
Male plug M12x1 (4-pin) / metal					M	1	0			
compact field housing										
stainless steel 1.4404 (316L)					8	5	0			
customer					9	9	9			consult
<b>Mechanical connection</b> <sup>2</sup>										
G1/2" DIN 3852					1	0	0			
G1/2" EN 837					2	0	0			
G1/4" DIN 3852					3	0	0			
G1/4" EN 837					4	0	0			
G1/2" DIN 3852 with <sup>3</sup>					F	0	0			
semi-flush sensor										
G1/2" DIN 3852 open pressure port					H	0	0			
1/2" NPT					N	0	0			
1/4" NPT					N	4	0			
customer					9	9	9			consult
<b>Seals</b>										
FKM							1			
EPDM							3			
NBR							5			
customer							9			consult
<b>Pressure port</b>										
Stainless steel 1.4404 (316L)							1			
PVDF <sup>4</sup>							B			
customer							9			consult
<b>Diaphragm</b>										
Ceramics Al <sub>2</sub> O <sub>3</sub> 96%							2			
customer							9			consult
<b>Special version</b>										
standard							0	0	0	
oxygen application <sup>5</sup>							0	0	7	
customer							9	9	9	consult

<sup>1</sup> standard: 2 m PVC cable without ventilation tube (permissible temperature: -5 ... 70°C)  
<sup>2</sup> metric threads and others on request  
<sup>3</sup> possible for nominal pressure ranges P<sub>N</sub> ≤ 25 bar  
<sup>4</sup> PVDF only with G1/2" DIN 3852 open pressure port (up to 60 bar)  
<sup>5</sup> oxygen application possible up to 25 bar and only with FKM-seal

This price list contains product specification; properties are not guaranteed. Detailed information about options are defined in the datasheet. Subject to change without notice.

